

The following structures and improvements are prohibited:

- 1. Covered moorage, boathouses, or other walled covered moorage. Covered boat lifts in conformance with other provisions in this section may be allowed. Existing enclosed moorage structures shall be considered nonconforming uses subject to the provisions of BLMC 16.56.150.
- 2. Skirting on any structure.
- 3. Over-water residential use, including houseboats, live-aboards, or other single- or multifamily dwelling units.
- 4. Launching rails.
- 5. New recreational floats and swimming platforms for private properties.

SMP Update Kick-off Meeting November 1, 2018

| Promistics | Management |
|--|-----------------|
| Description | Measurement |
| Area | T |
| Single property owner | 360 Square Feet |
| Shared by 2 property owners | 580 Square Feet |
| Shared by 4 or more property owners or dwelling units | 1,000 Square |
| | Feet |
| Maximum Length | |
| Fingers and floats | 20 Feet |
| Ells | 25 Feet |
| Maximum Width | |
| Portion of the walkway within 30 feet of the OHWM | 4 Feet |
| Portion of the walkway greater than 30 feet from the OHWM | 6 Feet |
| Ell and float | 6 Feet |
| Finger | 3 Feet |
| Ramp connecting a pier to a float | 3 Feet |
| Height | |
| Minimum height above the OHWM measured for the OHWM to the bottom of the stringers on the dock/pier | 1-1/2 Feet |
| Maximum height above the OHWM measured from the OHWM to the top of the decking | 5 Feet |
| Location of Specific Structures | -1 |
| Minimum distance of ells, fingers, floats, buoys, moorage buoys from shore as measured waterward of OHWM | 30 Feet |
| Minimum distance from decks/piers located on adjacent properties | 20 Feet |
| Minimum distance between piers | 12 Feet |




Figure 1: Diagram of Typical Pier/Dock Elements